

Correct as at 3rd June 2026. It may be superseded at any time.

Extract taken from: In-service certification (WoF and CoF) > Motorcycles > Vision > Glazing

5-1 Glazing

Reasons for rejection

Permitted equipment

1. Any glazing is not a transparent material that does not shatter.

Glazing condition

2. A piece of glazing is not mechanically sound, or is not securely affixed to the vehicle.
3. A windscreen (Note 1) (not a wind deflector) or front side window is so dirty or obstructed that the driver's vision is impaired.
4. A windscreen (not a wind deflector) has damage that prevents the wiper blades from working properly.
5. A windscreen has scratches, discolouration or other defects that unreasonably impair the driver's vision or compromise the strength of the windscreen.

Condition within the critical vision area (CVA)

6. The critical vision area (CVA) of a windscreen (Figure 5-1-1) is damaged (Note 2) (apart from scratching and surface pitting that does not affect the driver's vision such as small stone marks).

Condition outside the CVA (Note 10)

7. A windscreen (not a wind deflector) has damage of a type and exceeding the dimensions in Figure 5-1-2.
8. Any damage to a windscreen (not a wind deflector) that extends through more than one layer of glass.

Glazing performance

9. The overall visible light transmittance (VLT) (Note 4) of a windscreen is less than 70%.
10. The overall VLT of a front side window is less than 35%.
11. Glazing has a mirrored effect sufficient to dazzle other road users (unless it is OE and has an approved standard marking).
12. A modification:
 - a) unreasonably impairs the rider's vision through the windscreen or front side window, or
 - b) adversely affects the strength or mechanical performance of the glazing on the vehicle.

Permitted modifications

13. A modification that affects glazing is not within the limits in Table 5-1-1.

Windscreen repair

14. A windscreen that has been rejected for a WoF or CoF has been repaired and re-presented without the required documentation (Note 5)

Note 1

Windscreen means all glazing extending across the front of a vehicle that is not parallel to the vehicle's centreline but does not include a wind deflector.

Note 3

Laminated glass means glazing consisting of two or more pieces of sheet glass, plate glass or float glass bonded together by one or more intervening layers of plastic material.

Note 4

Visible light transmittance (VLT) is the proportion of visible light that passes through glazing, measured perpendicular to the glazing. Overall VLT is the VLT of the glazing together with any overlays.

Note 5

When a windscreen has been rejected for a WoF or CoF, repaired, and then re-presented for inspection, the repair must be certified to AS/NZS2366 1999, AS2366 1990 or NZS5470 1993. Proof of certification is the receipt issued in accordance with the relevant standard by the repairer. For AS/NZS2366 1999, the windscreen repair invoice must include:

- a) invoice number
- b) date of repair
- c) date of invoice (if different from date of repair)
- d) trading name and address of repairer
- e) name or identification of person performing the repair
- f) make of vehicle
- g) registration number of vehicle, or if registration number is unavailable, then the vehicle identification number (VIN) or chassis number
- h) details of work carried out
- i) type and location of repaired damage on the windscreen (it is recommended that this be marked on a schematic windscreen on the invoice form))
- j) in the case of repairs performed to this standard, a statement that the repairs have been made in accordance and comply with AS/NZS 2366.1 using a repair system that complies with AS/NZS 2366.2.

Note 6

Overlay means a transparent, translucent or opaque self-adhesive or clinging film that is applied to large areas, or the whole, of a piece of glazing, including anti-glare band overlays, stoneguard overlays.

Note 7

Sticker means a self-adhesive or clinging film, with or without print on it, that is applied for purposes such as advertising, identification, information, or for aesthetic or legal reasons.

Note 8

Anti-glare band overlay means a tinted overlay that is transparent and that is applied along the top edge of the windscreen for the purpose of reducing glare from the sun.

Note 9

Stoneguard overlay means a clear overlay that is transparent and that is applied along the bottom edge of the windscreen for the purpose of preventing damage to the windscreen from stones and other debris thrown up by other vehicles.

Note 10


Any OE opaque edging (usually black) is not considered part of the windscreen when determining the boundaries of the CVA, or the areas permitted for stickers, print on an anti-glare band, or radio antennae.

Table 5-1-1. Permitted modifications

Fitting of or modification to:	Modification permitted provided that:
<p>Overlays (Note 6)</p> <p>(see also below for overlays on windscreens, front side windows, rear and rear side windows, and sun roofs)</p>	<ul style="list-style-type: none"> • overlays do not: <ul style="list-style-type: none"> – have any bubbling or other defects that could unreasonably impair vision, or – have a mirrored effect that is sufficient to dazzle other road users, or – affect the performance of any high-mounted stop lamps fitted to the vehicle.
<p>Windscreens (Note 1):</p>	
<p>Stickers (Note 7)</p>	<ul style="list-style-type: none"> • stickers are wholly within 100 mm of the top or bottom edge, or 50 mm of the side edges, unless required or permitted by legislation, eg: <ul style="list-style-type: none"> – a licence label – a road user licence label – a WoF label – an alternative fuel sticker – a parking permit or other document issued by the local authority – learner L-plates (in sticker format) provided the driver's vision is not unreasonably affected.
<p>Anti-glare band overlay (Note 8)</p>	<ul style="list-style-type: none"> • the overlay is transparent, and <ul style="list-style-type: none"> – does not extend below the bottom edge of the vehicle's OE sun visors when they are folded down as far as possible towards the windscreen, and – does not contain print below a line that is 100 mm below and parallel to the top edge of the windscreen.
<p>Radio antennae</p>	<ul style="list-style-type: none"> • antennae are wholly within 100 mm of any edge.
<p>Front side windows:</p>	

Fitting of or modification to:	Modification permitted provided that:
Transparent overlays	<ul style="list-style-type: none"> the overall visible light transmittance (VLT) is not reduced to below 35%.
Stickers	<ul style="list-style-type: none"> stickers are wholly within 100 mm of the bottom edge, or 50 mm of any other edge, unless required or permitted by legislation.
Radio antennae	<ul style="list-style-type: none"> antennae are wholly within 100 mm of any edge.
Rear and rear side windows (behind the driver's seat):	
Overlays and other modifications	<ul style="list-style-type: none"> the vehicle is equipped on both sides with external rear-view mirrors.
Stickers	<ul style="list-style-type: none"> stickers may be applied anywhere on the glazing, but if not wholly within 100 mm of any edge, the vehicle must be equipped on both sides with external rear-view mirrors.
Radio antennae	<ul style="list-style-type: none"> in-service requirements for condition and performance are met.
Monsoon shields	<ul style="list-style-type: none"> in-service requirements for condition and performance are met.
Electric demisters	
Sunroofs: overlays and stickers applied anywhere on the glazing, radio antennae and electric demisters	
Any modification for the purposes of law enforcement or the provision of emergency services	

Figure 5-1-1. Windscreen critical vision area (CVA)



To be measured from the inside of the vehicle from the point where the glass is visible (ie after any seals)

Figure 5-1-2. Types and maximum sizes of windscreen damage (Note 2).


(see also Figure 5-1-3)

COMBINATION DAMAGE

Combination: same type

Diameter of the smallest circle around all incidences is measured and maximum diameter applied.


Example:
Two craters:
Maximum diameter
5 mm for both
craters together.



Combination: same + different types

Each type is measured and maximum diameter applied separately.

Example:
Two craters + crack:
Maximum diameter
5 mm for two craters;
100 mm for the crack,
whichever applies.



Combination: different types

Each type measured
and maximum diameter
applied.

Example:
Bullseye + crack:
Maximum diameter
20 mm for the bullseye;
100 mm for the crack,
whichever applies.




Figure 5-1-3. Types and maximum sizes of windscreen damage (incl. actual maximum sizes)


Note Due to different screen resolutions and sizes the image may not be displayed at actual size.

COMBINATION DAMAGE

Combination: same type

Diameter of the smallest circle around all incidences is measured and maximum diameter applied.


Example:
Two craters:
Maximum diameter
5 mm for both
craters together.



Combination: same + different types

Each type is measured and maximum diameter applied separately.


Example:
Two craters + crack:
Maximum diameter
5 mm for two craters;
100 mm for the crack,
whichever applies.



Combination: different types

Each type measured
and maximum diameter
applied.

Example:
Bullseye + crack:
Maximum diameter
20 mm for the bullseye;
100 mm for the crack,
whichever applies.



Summary of legislation

Applicable legislation

- [Land Transport Rule: Glazing, Windscreen Wipe and Wash, and Mirrors 1999](#)

Permitted glazing

Glazing markings

1. All glazing must be transparent material of a kind that does not shatter.

Glazing condition

2. Glazing must be mechanically sound, strong, and securely affixed to the vehicle.
3. A windscreen and front side windows must be clean and free of obstruction to ensure the driver has sufficient vision through the glazing to operate the vehicle safely.
4. A windscreen must not have scratches and other defects that:
 - a) unreasonably impair vision, or
 - b) compromise its strength.

5. A laminated windscreen must not show signs of discolouration that could unreasonably impair the driver's vision.

Glazing performance

6. A windscreen visible light transmittance (VLT) must be at least 70%.

7. Front side windows VLT must be at least 35%.

8. Glazing must not have a mirrored effect sufficient to dazzle other road users.

9 A modification must not:

a) unreasonably impair vision through the windscreen or a front side window, or

b) adversely affect the strength or mechanical performance of the glazing on the vehicle.

Permitted modifications

10. A modification that affects glazing is permitted if within the limits in Table 5-1-1.

Windscreen repair

11. A repair to a windscreen carried out on or after 1 January 1997 must comply with whichever of the following standards is applicable at the date of repair:

a) New Zealand Standard 5470: 1993, Code of Practice for Automotive Windscreen Repair (superseded by Australian Standard/New Zealand Standard 2366: 1999, Windscreen Repairs), or

b) Australian Standard 2366-1990, Repair of Laminated Glass Windscreens Fitted to Road Vehicles (superseded by Australian Standard/New Zealand Standard 2366: 1999, Windscreen Repairs).