

Correct as at 24th April 2026. It may be superseded at any time.

Extract taken from: In-service certification (WoF and CoF) > Motorcycles > Vehicle interior > Head restraints

## 7-3 Head restraints

### Reasons for rejection

#### Condition and performance

1. The external surfaces and padding of a head restraint have deteriorated to the extent that they are likely to injure a vehicle occupant.
2. An adjustable head restraint is unable to remain locked in its adjusted position.

#### Modification

3. A modification (Note 1) affects a head restraint, and:
  - a) is not excluded from the requirements for LVV specialist certification (Table 7-3-1), and
  - b) is missing proof of LVV specialist **or accepted overseas** certification, ie:
    - i. the vehicle is not fitted with a valid LVV certification plate, or
    - ii. the operator is not able to produce a valid modification declaration or authority card **, or**
    - iii. **the vehicle has not been certified to an accepted overseas system as described in [Technical bulletin 13](#).**

#### Note 1 Definitions

**Modify** means to change a vehicle from its original state by altering, substituting, adding or removing a structure, system, component or equipment, but does not include repair.

**Repair** means to restore a damaged or worn vehicle, its structure, systems, components or equipment to within safe tolerance of its condition when manufactured, including replacement with undamaged or new structures, systems, components or equipment.

**Table 7-3-1. Modifications that do not require LVV certification**

Fitting of or modification to:	LVV certification is never required:
Head restraint removal	<ul style="list-style-type: none"> <li>• in-service requirements for condition and performance must be met.</li> </ul>
Any modification for the purpose of law enforcement or the provision of emergency services	

# Summary of legislation

## Applicable legislation

- [Land Transport Rule: Head Restraints 2002](#).

## Permitted equipment

1. A motor vehicle may be fitted with head restraints.

## Condition and performance

2. The external surfaces and padding of a head restraint must not have deteriorated to the extent that the likelihood of injury to an occupant of the vehicle is increased.
3. An adjustable head restraint must remain able to be adjusted and locked into position.

## Modification

4. A modification that affects a head restraint must be inspected and certified by an LVV specialist certifier, unless the vehicle:
  - a) is excluded from the requirement for LVV specialist certification (Table 7-3-1), and
  - b) has been inspected in accordance with the requirements in this manual, including those for equipment, condition and performance.

Page amended **1 December 2016** (see [amendment details](#)).